

AGRIMAX TERIS - Technical Specifications



Description

Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance - thus extending the product life-cycle – also in harsh conditions and if there are stubbles in the fields.

UM

International Standard

Construction



RADIAL

Machinery

Agriculture: Cotton Picker • Harvester

Version	STANDARD
Type	TL
Tyre Size	900/60 R 32 CHO
LI/SS	185 A8/182 B

Dimensions International Standard

Section Width (mm)	875
Overall Diameter (mm)	1910
Static Loaded Radius (mm)	875
Rolling Circumference (mm)	5775
SRI (mm)	900
Rim Rec	DW 27 B
Rim Alt	DW 28 B ; DW 30 B
ECE	E4-106R-001433

Load capacity (Kg)

km/h / bar	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0
50	3375	3825	4800	5325	5925	6375	6975	7500	7990	8500
40	3715	4210	5280	5860	6520	7015	7675	8250	8695	9250
30	3975	4505	5655	6270	6980	7510	8215	8830	9305	9900
15 Cyc	6130	6945	8715	9670	10760	11575	12665	13615	14350	15265
10 Cyc	6685	7575	9505	10545	11735	12625	13815	14850	15655	16650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 6/3/2025 11:44 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..